


SUBMITTED MODEL NO.
FCS-100-VRMZURNNS-1.25
CHROME FINISH

JOB NAME	ITEM	Retrofits Zurn Z7000-12 with 1.25 inch-20 UNF Male Threads
SUBMITTED AS SHOWN		
SUBMITTED AS NOTED		




*DIMENSIONS IN INCHES

SPECIFICATIONS	NOTES
① FCS™ Patented Stainless Steel Single Non-Clogging Nozzle. Non-Swivel Body. ② Non-Clogging Silicone Flow Control Diaphragm 1.25 GPM at 30-80 psi. Pressure Compensating. ③ Threads: 1.25"-20 UNF Male. ④ All Metal Construction; Brass and Stainless Steel. Fully Drains After Each Use. Naturally Antibacterial. Chrome Plated. Wt: .40 lbs. ⑤ Retrofits Zurn Z7000-12 & Other Wall Receivers With 1.25"-20 UNF Female Threads. ⑥ Vandal and Ligature Resistant Set Screws: 1/16" Hex Stainless Steel. ⑦ Certifications: A112.18.1, and WaterSense. California Compliant. ⑧ Compliant with Buy American Act (BAA). U.S. Patent 7,185,830 B2 and Patent Pending.	Installation: Use Spanner Wrench with 3/16" pin.

SUBMITTED MODEL NO.
FCS-100-VRMZURNNS-1.5
CHROME FINISH

JOB NAME	ITEM	Retrofits Zurn Z7000-12 with 1.25 inch-20 UNF Male Threads
SUBMITTED AS SHOWN		
SUBMITTED AS NOTED		




*DIMENSIONS IN INCHES

SPECIFICATIONS	NOTES
① FCS™ Patented Stainless Steel Single Non-Clogging Nozzle. Non-Swivel Body. ② Non-Clogging Silicone Flow Control Diaphragm 1.5 GPM at 30-80 psi. Pressure Compensating. ③ Threads: 1.25"-20 UNF Male. ④ All Metal Construction; Brass and Stainless Steel. Fully Drains After Each Use. Naturally Antibacterial. Chrome Plated. Wt: .40 lbs. ⑤ Retrofits Zurn Z7000-12 & Other Wall Receivers With 1.25"-20 UNF Female Threads. ⑥ Vandal and Ligature Resistant Set Screws: 1/16" Hex Stainless Steel. ⑦ Certifications: A112.18.1, WaterSense, and WaterMark. California Compliant. ⑧ Compliant with Buy American Act (BAA). U.S. Patent 7,185,830 B2 and Patent Pending.	Installation: Use Spanner Wrench with 3/16" pin.

SUBMITTED MODEL NO.
FCS-100-VRMZURNNS-1.8
CHROME FINISH

JOB NAME	ITEM	Retrofits Zurn Z7000-12 with 1.25 inch-20 UNF Male Threads
SUBMITTED AS SHOWN		
SUBMITTED AS NOTED		




*DIMENSIONS IN INCHES

SPECIFICATIONS	NOTES
① FCS™ Patented Stainless Steel Single Non-Clogging Nozzle. Non-Swivel Body. ② Non-Clogging Silicone Flow Control Diaphragm 1.8 GPM at 30-80 psi. Pressure Compensating. ③ Threads: 1.25"-20 UNF Male. ④ All Metal Construction; Brass and Stainless Steel. Fully Drains After Each Use. Naturally Antibacterial. Chrome Plated. Wt: .40 lbs. ⑤ Retrofits Zurn Z7000-12 & Other Wall Receivers With 1.25"-20 UNF Female Threads. ⑥ Vandal and Ligature Resistant Set Screws: 1/16" Hex Stainless Steel. ⑦ Certifications: A112.18.1, and WaterSense. California Compliant. ⑧ Compliant with Buy American Act (BAA). U.S. Patent 7,185,830 B2 and Patent Pending.	Installation: Use Spanner Wrench with 3/16" pin.

SUBMITTED MODEL NO.
FCS-100-VRMZURNNS-2.0
CHROME FINISH

JOB NAME	ITEM	Retrofits Zurn Z7000-12 with 1.25 inch-20 UNF Male Threads
SUBMITTED AS SHOWN		
SUBMITTED AS NOTED		



*DIMENSIONS IN INCHES

SPECIFICATIONS	NOTES
① FCS™ Patented Stainless Steel Single Non-Clogging Nozzle. Non-Swivel Body. ② Non-Clogging Silicone Flow Control Diaphragm 2.0 GPM at 30-80 psi. Pressure Compensating. ③ Threads: 1.25"-20 UNF Male. ④ All Metal Construction; Brass and Stainless Steel. Fully Drains After Each Use. Naturally Antibacterial. Chrome Plated. Wt: .40 lbs. ⑤ Retrofits Zurn Z7000-12 & Other Wall Receivers With 1.25"-20 UNF Female Threads. ⑥ Vandal and Ligature Resistant Set Screws: 1/16" Hex Stainless Steel. ⑦ Compliant with Buy American Act (BAA). U.S. Patent 7,185,830 B2 and Patent Pending.	Installation: Use Spanner Wrench with 3/16" pin.